

Internal Hot Swap HDD Enclosures


BP-46TM

Dimensions(mm)	: 180(L) x 146(W) x 42(H)
Interface	: SATA I,II,III · SAS I,II
Power Connector	: SATA Power Connector x 1
Hot Swap	: Supporting Plug & Play
Support RAID	: N/A
Support Disks	: 2.5" SATA(SAS)HDD / SSD x 4
Cooling Fan	: 4cm Fan x 2


BP-86TM

Dimensions(mm)	: 180(L) x 146(W) x 86(H)
Interface	: SATA I,II,III · SAS I,II
Power Connector	: SATA Power Connector x 2
Hot Swap	: Supporting Plug & Play
Support RAID	: N/A
Support Disks	: 2.5" SATA(SAS)HDD / SSD x 8
Cooling Fan	: 7cm Fan x 1


BP-126TM

Dimensions(mm)	: 180(L) x 146(W) x 126(H)
Interface	: SATA I,II,III · SAS I,II
Power Connector	: SATA Power Connector x 3
Hot Swap	: Supporting Plug & Play
Support RAID	: N/A
Support Disks	: 2.5" SATA(SAS)HDD / SSD x 12
Cooling Fan	: 7cm Fan x 1


BP-36TL

Dimensions(mm)	: 195(L) x 146(W) x 84.5(H)
Interface	: SATA I,II,III · SAS I,II
Power Connector	: SATA Power Connector x 2
Hot Swap	: Supporting Plug & Play
Support RAID	: N/A
Support Disks	: 3.5" SATA(SAS)HDD / SSD x 3
Cooling Fan	: 7cm Fan x 1


BP-46TL

Dimensions(mm)	: 198(L) x 146(W) x 126(H)
Interface	: SATA I,II,III · SAS I,II
Power Connector	: SATA Power Connector x 2
Hot Swap	: Supporting Plug & Play
Support RAID	: N/A
Support Disks	: 3.5" SATA(SAS)HDD / SSD x 4
Cooling Fan	: 8cm Fan x 1


BP-56TL

Dimensions(mm)	: 198(L) x 126(W) x 146(H)
Interface	: SATA I,II,III · SAS I,II
Power Connector	: SATA Power Connector x 2
Hot Swap	: Supporting Plug & Play
Support RAID	: N/A
Support Disks	: 3.5" SATA(SAS)HDD / SSD x 5
Cooling Fan	: 8cm Fan x 1


BP-16TM

Dimensions(mm)	: 175(L) x 146(W) x 42(H)
Interface	: SATA I,II,III · SAS I,II
Power Connector	: SATA Power Connector x 1
Hot Swap	: Supporting Plug & Play
Support RAID	: N/A
Support Disks	: 3.5" SATA(SAS)HDD / SSD x 1
Cooling Fan	: Fanless


BP-36TM

Dimensions(mm)	: 202(L) x 146(W) x 86(H)
Interface	: SATA I,II,III · SAS I,II
Power Connector	: SATA Power Connector x 2
Hot Swap	: Supporting Plug & Play
Support RAID	: N/A
Support Disks	: 3.5" SATA(SAS)HDD / SSD x 3
Cooling Fan	: 8cm Fan x 1


BP-56TM

Dimensions(mm)	: 217(L) x 126(W) x 146(H)
Interface	: SATA I,II,III · SAS I,II
Power Connector	: SATA Power Connector x 2
Hot Swap	: Supporting Plug & Play
Support RAID	: N/A
Support Disks	: 3.5" SATA(SAS)HDD / SSD x 5
Cooling Fan	: 8cm Fan x 1



BP-1041SS

Dimensions(mm)	: 175(L) x 146(W) x 42(H)
Interface	: SATA
Power Connector	: Standard 15Pin Connector x 1
Hot Swap	: Supporting Plug & Play
Support RAID	: N/A
Support Disks	: 2.5"HDD x 4
Cooling Fan	: 4cm Fan x 2



BP-1060SA

Dimensions(mm)	: 175(L) x 146(W) x 42(H)
Interface	: SATA
Power Connector	: Standard 4Pin Connector x 1
Hot Swap	: Supporting Plug & Play
Support RAID	: N/A
Support Disks	: 2.5"HDD x 6
Cooling Fan	: 4cm Fan x 2



RE-2221SI

Dimensions(mm)	: 146(L) x 101(W) x 25(H)
Interface	: USB+SATA
Power Connector	: 1xSATA 15Pin Connector
Hot Swap	: Supporting Plug & Play
Support RAID	: RAID 0,1
Support Disks	: 2.5"HDD x 2
Cooling Fan	: Fanless



BP-47SS

Dimensions(mm)	: 202(L) x 146(W) x 42(H)
Interface	: SATA I,II,III · SAS I,II
Power Connector	: SATA Power Connector x 1
Hot Swap	: Supporting Plug & Play
Support RAID	: N/A
Support Disks	: 2.5" HDD(SSD) x 4
Cooling Fan	: 4cm Fan x 2



BP-87SS

Dimensions(mm)	: 199(L) x 146(W) x 85(H)
Interface	: SATA I,II,III · SAS I,II
Power Connector	: SATA Power Connector x 2
Hot Swap	: Supporting Plug & Play
Support RAID	: N/A
Support Disks	: 2.5" HDD(SSD) x 8
Cooling Fan	: 8cm Fan x 1



BP-127SS

Dimensions(mm)	: 201(L) x 146(W) x 127(H)
Interface	: SATA I,II,III · SAS I,II
Power Connector	: SATA Power Connector x 2
Hot Swap	: Supporting Plug & Play
Support RAID	: N/A
Support Disks	: 2.5" HDD(SSD) x 12
Cooling Fan	: 8cm Fan x 1



PCI Bracket Option

BP-18TM

Dimensions(mm)	: 138(L) x 72.5(W) x 11.5(H)
Interface	: SATA I,II,III · SAS I,II
Power Connector	: Mini 4Pin Connector x1
Hot Swap	: Supporting Plug & Play
Support RAID	: N/A
Support Disks	: 2.5" HDD(SSD) x1 Less Than 7mm
Cooling Fan	: N/A



BP-48TM

Dimensions(mm)	: 138(L) x 72.5(W) x 40.2(H)
Interface	: SATA I,II,III · SAS I,II
Power Connector	: SATA Power Connector x1
Hot Swap	: Supporting Plug & Play
Support RAID	: N/A
Support Disks	: 2.5" HDD(SSD) x4 Less Than 7mm
Cooling Fan	: N/A



BP-88TM

Dimensions(mm)	: 159(L) x 146(W) x 42(H)
Interface	: SATA I,II,III · SAS I,II
Power Connector	: SATA Power Connector x2
Hot Swap	: Supporting Plug & Play
Support RAID	: N/A
Support Disks	: 2.5" HDD(SSD) x8 Less Than 7mm
Cooling Fan	: 4cm Fan x1