

GA6602

i3,i5,i7
System

KIOSK

POS
PC

POS PC —



Rack Mount —




Wall Mount —

A
Type1 x Slim ODD Bay
+ 1 x 2.5" HDD Bay


2 x USB

Mini-ITX M/B

Low Profile
PCI CardB
Type1 x Slim ODD Bay
+ 1 x 2.5" HDD Bay

2 x USB

Mini-ITX M/B




Low Profile PCI Card

C
Type1 x 3.5" HDD Bay or
1 x 2.5" HDD Bay

2 x USB

Mini-ITX M/B

Low Profile
PCI Card

Accessories

Mini-ITX
M/BFSP
180-50LGSlim
Optical DriveSATA ODD
Cable5cm Single
Fan5cm
Twin FanWall Mount
Kits

Rack Mount



Specifications

Model	GA6602iBK
Form Factor	Mini-ITX Case
Chassis Dimensions	215 (D) x 250 (W) x 85 (H)mm = 4.56 L , with front panel
Drive Bays	Flexible Combination as state form right
Front	2 x USB(V2.0) , Power SW , Power/HDD LED
Power Supply	FlexATX 180W (CUL/TUV/ PSE/CB/CE/FCC,ErP,Active PFC)
PCI Slot	Low Profile PCI or PCI-E
System Fan	• 1 x 50 x 50 x 10mm Twin Fan (Side) • 1 x 50 x 50 x 10mm Single Fan (Side)
Additional Port	3 x Serial Port (Max)
Packing	1pc / 2.50 kgs / 3.00 kgs / 0.84'
Options	• Wall Mount Kits • Rack Mount Kits • Vent Holes on top cover • CPU Cooler : • Low profile — GA6602A , GA6602C w/3.5" HDD Bay • Intel Standard — GA6602B , GA6602C w/2.5" HDD Bay
Applications	i3 / i5 / i7 System , POS PC , KIOSK

System Configurations

Storage Choice	1.	2.	3.	4.
Slim ODD	1	-	1	-
3.5" HDD	-	-	-	1
2.5" HDD	1	2	1	-
Printer Port	1	1	1	1
PCI	1	1	1	1
COM Hole	3	3	3	2
Wifi Hole	2	2	2	2
DVI Hole	-	-	-	-
CF	Front			
	Bottom	Y	Y	Y
Type	A		B	C