

DC Power / AC Power



AC-ITX55

Descriptions	: AC/DC Open Frame Power				
Input DC Voltage	: 100~240Vac				
Output(W)	: 55W				
Operating Temperature	: 0°C ~50°C				
Dimensions	: 180(L) x 40(W) x 40(H) mm				
Maximum Output					
Output Voltage(V)	5VSB	+3.3V	+5V	+12V	-12V
Output Current(A)	1	4	7	3.5	0.2



DD-ITX60

Descriptions	: DC Open Frame Power				
Input DC Voltage	: 12V				
Output(W)	: 60W				
Operating Temperature	: 0°C ~40°C				
Dimensions	: 100(L) x 30(W) x 23(H) mm				
Maximum Output					
Output Voltage(V)	5VSB	+3.3V	+5V	+12V	-12V
Output Current(A)	1	3	5	2	0.2



DD-ITX90

Descriptions	: DC Open Frame Power				
Input DC Voltage	: 12V				
Output(W)	: 90W				
Operating Temperature	: 0°C ~40°C				
Dimensions	: 155(L) x 45(W) x 28(H) mm				
Maximum Output					
Output Voltage(V)	5VSB	+3.3V	+5V	+12V	-12V
Output Current(A)	1.4	3.1	4.2	4.2	0.14



DD-ITX120

Descriptions	: DC Open Frame Power				
Input DC Voltage	: 12V				
Output(W)	: 120W				
Operating Temperature	: 0°C ~40°C				
Dimensions	: 155(L) x 45(W) x 28(H) mm				
Maximum Output					
Output Voltage(V)	5VSB	+3.3V	+5V	+12V	-12V
Output Current(A)	1.7	3.8	5.1	5.9	0.17



AC-FLX180

Descriptions	: FLEX Power				
Input DC Voltage	: 100~240Vac				
Output(W)	: 180W				
Operating Temperature	: 0°C ~50°C				
Dimensions	: 150(L) x 81.5(W) x 40.5(H) mm				
Maximum Output					
Output Voltage(V)	5VSB	+3.3V	+5V	+12V	-12V
Output Current(A)	2	14	16	14	0.3



AC-SFX400

Descriptions	: Micro ATX Power				
Input DC Voltage	: 115V/230V				
Output(W)	: 400W				
Operating Temperature	: 0°C ~50°C				
Dimensions	: 100(L) x 125(W) x 63.5(H) mm				
Maximum Output					
Output Voltage(V)	5VSB	+3.3V	+5V	+12V1	-12V2
Output Current(A)	2.5	21	22	17	16